



## Locking 19" Cat6 Unshielded Patch Panel

24 Port, UTP, 1U, Top Entry Punch Down, Locking Function

Part No.: **720564**

For extra security in your server room patch panels, I.T. Department test bench or network access points, the new range of Locking Function Patch Panels, Keystones, Inline Couplers and mount boxes will inevitably be of interest to you and your I.T. team. Recommended for all businesses and currently utilized in financial institutions, hotels, airports, schools, hospitals and retail stores.

Excellent in areas where vibration can loosen a standard RJ45 connection such as in trains, aircraft and in the vicinity of vibrating machinery.

### Features:

- Extra security with locking function
- Solid and reliable terminations for copper cabling featuring a minimum of 50 micron gold-plated jack contacts
- Top-entry punch-down blocks simplify installation
- Compatible with Krone & 110 punch-down tools
- Supports 22 to 26 AWG stranded and solid wire
- Meets 19" rackmount standards
- Lifetime Warranty

### Specifications:

#### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000Base-T Gigabit Ethernet)
- IEEE 802.3an (10GBASE-T)

#### Certifications

- UL listed
- RoHS compliant

#### Environmental

- Dimensions: 482 mm (W) x 44 mm (H) x 115 mm (D) (19 x 1.7 x 4.5 in.)
- Horizontal distance between left and right mounting holes: 465 mm (18.3 in.)
- Vertical distance between top and bottom mounting holes: 32 mm (1.25 in.)
- Weight: 1.4 kg (3 lbs.)
- Operating temperature: -40 – 70°C (-40 – 158°F)

*For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).*

*All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.*

## Package Contents

- Patch Panel
- Key Tool

