SuperSpeed USB 3.0 to SATA and CFAST Adapter

USB-A Male to SATA 2.5" Male and CFAST 2.0 Connector, 5 Gbps Data Transfer Rate, Black
Part No.: 151825

Quickly transfer, store and archive important data.

The Manhattan SuperSpeed USB 3.0 to SATA and CFAST Adapter connects a SATA Hard-disk Drive (HDD) or Solid-state Drive (SSD) and a CFAST memory card to a desktop and notebook computer using a USB 3.0 type-A port. As consumer demand for data security and data recovery increases, the Manhattan SuperSpeed USB 3.0 to SATA and CFAST Adapter offers masterful handling of large amounts of data during its transfer from drive and memory card to computer and vice versa. Its compatibility with all types of 2.5" hard drives and CFAST 2.0 memory cards makes it a versatile tool for professional and home users alike. Easy to install and use, its plug-and-play and hot-swap capabilities provide a convenient method to transfer, store data and test hard drives.

Features:

- Provides fast data access to a SATA drive and a CFAST memory card
- Supports data transfer between SATA, CFAST and SuperSpeed USB 3.0 up to 5 Gbps
- Offers SATA-drive and CFAST-memory-card data transfer, both individually and simultaneously
- Supports an external 2.5" SATA Hard-Disk Drive (HDD) or Solid-State Drive (SSD) up to 2 TB
- Supports external CFAST 2.0 memory card
- Compatible with Windows and Mac systems
- Plug and Play
- Three-year warranty

Specifications:

Standards and Certifications
- USB 3.0
- USB 2.0
- USB 1.1
- Complies with ATA/ATAOI-100 spec v1.0 standards
- SATA I, II, III
- FCC
- CE
- EuP
- WEEE

General
- USB 3.0 type-A male; SATA L-type male and CFAST connector
- SuperSpeed USB transfer interface
- 5 Gbps maximum transfer rate
- Supports SATA 2.5" and CFAST 2.0 memory card
- LED: blue flashes indicate data transfer

Physical
- Dimensions: 22.9 x 4.2 x 1.5 cm (9.02 x 1.65 x 0.59 in.)
- Cable length: 16.8 cm (6.61 in.)
- Weight: 30 g (1.05 oz.)

System Requirements
- Available USB 3.0 type-A port
- Windows XP/Vista/7/8/10 or Mac OSX

Operating Environment
- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

Package Contents
- SuperSpeed USB 3.0 to SATA and CFAST Adapter
- Quick Installation Guide