LVK040_DATASHEET

Option Bullet Camera



Pack Contains

- Bullet Camera
- 1x UTP Cable (20m)

Model: Uniview 2122SR3-PF40-C (4mm)

2MP Mini Fixed Bullet Network Camera + 1 UTP cable (20m)

Features

- Day/night functionality
- Smart IR , up to 30 m (98 ft) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- 3D DNR (Digital Noise Reduction)

Compression

- H.265, H.264, MJPEG
- Embedded smart algorithm
- Triple streams
- 9:16 corridor format

Network

- ONVIF Conformance

Structure

- Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- Wide voltage range of ±25%
- IP67

LVK040_DATASHEET

Specifcations

Camera

- Sensor: 1/2.7", 2.0 megapixel, progressive scan, CMOS
- Lens: 4.0mm @F1.8
- Angle of View: 84.8°
- Shutter: Auto/Manual, 1/6~1/100000 s
- Min. Illumination:
    - Colour: 0.02 Lux (F1.8, AGC ON)
    - 0 Lux with IR on
- IR Range: Up to 30m (98 ft) IR range
- Day/Night: IR-cut filter with auto switch (ICR)
- S/N: >52dB
- WDR: Digital
- Noise Reduction: 2D/3D

Video

- Max. Resolution: 1920×1080
- Video Compression: H.265, H.264, MJPEG
- Frame Rate: 1080P (1920×1080): Max. 30 fps; 720P (1280×720): Max. 30 fps; D1 (720×576): Max. 8 fps
- Video Streaming: Triple
- 9:16 Corridor Mode: Supported
- ROI: Supported
- HLC: Supported
- Evaluative Metering: Supported
- OSD: Up to 8 OSDs
- Motion Detection: Up to 2 areas
- Privacy Mask: Up to 8 areas

Smart

- Behavior Detection: Intrusion, crossing line, motion detection
- Intelligent Identification: Face detection, Defocus, Scene Change
- Statistical Analysis: People counting

Network

- Protocols: L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x
- Compatible Integration: ONVIF, API

Interface

- Network: 1 RJ45 10M/100M Base-TX Ethernet

LVK040_DATASHEET

General

- Power:
    - 12 V DC, or PoE (IEEE802.3 af)
    - Power consumption: Max 6.4 W
- Dimensions (L × W × H): 157.3 × 62.4 ×63 mm (6.2” × 2.5” × 2.5”)
- Weight: 0.45 kg (0.99 lb)
- Working Environment: -35°C ~ +60°C (-31°F ~ 140°F), Humidity = 95% RH(non-condensing)
- Ingress Protection: IP67