

REV.	DESCRIPTION	ENG.	APPROVAL
B	Change CONN		



USBAM (NICKEL PLATED)
BLACK MOLDING:283
TOL:±0.5mm

USBAF (NICKEL PLATED)
BLACK MOLDING:314
TOL:±0.5mm



ZIP BAG(50*70mm)

PIN ASSIGNMENT:

P1	1	2	3	4	64
P2	1	2	3	4	64
	RED	WHITE	GREEN	BLACK	BRAID
		#28	#28		
		PAIR			

OPEN/SHORT TEST: 100% TEST.
INSULATION: 5M.

No.	Description	Qty
7	ZIP BAG(50*70mm)	1PCS
6	4-40# Screw(#4*10PM)	2PCS
5	BLACK 45P PVC	20G
4	4-40# Hex Nuts(5.0*4.0)	2PCS
3	USBAF (NICKEL PLATED)	1PCS
2	USBAM (NICKEL PLATED)	1PCS
1	UL2725,2.0VER,28#*1P+24#*2C+AL+B(AM),OD=4.5mm,BLACK COLOR,PVC JACKET.	1PCS

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INTRACOM Asia Co.,Ltd. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF INTRACOM Asia Co.,Ltd.

UNLESS OTHERWISE SPECIFIED:DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE:±1°

TOLERANCE(INCH)		TOLERANCE(MM)	
x	±0.02"	x	±0.5mm
x.x	±0.01"	x.x	±0.20mm
x.xx	±0.008"	x.xx	±0.15mm
x.xxx	±0.005"	x.xxx	±0.10mm

INTRACOM

TITLE:	APPD				
	Check	XIE			
CUSTOMER:	Drawer	L.L	Date 2014.3.25		
CUSTOMER P/N:	Unit	mm	Projection		
ICT P/N:	Scale	1:1	Size.	A4	
DWG.NO: 323871-600000	Sheet	1 of	REV.	B	