

SuperSpeed+ USB-C 3.1 to VGA Converter

C Male to VGA Female, Black

Part No.: 151771

Easily connect a USB type-C source with a VGA display
The Manhattan USB 3.1 to VGA Converter establishes a fast, simple and convenient link between newer USB type-C equipped media sources (computers, tablets, etc.) and existing VGA displays (monitors, projectors, etc.). The Manhattan USB 3.1 to VGA Converter is easy and quick to install--no complicated configuration or setup required. This bus-powered, cost-effective and reliable solution allows users to transition to USB type-C content without the expense of upgrading to newer and costly monitors and projectors. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and work spaces neat and orderly. Extend the service life of your equipment, and fully realize the investment and value of legacy VGA displays, projectors and peripherals with USB 3.1 to VGA Converters.

Features:

- Converts a USB signal to a VGA display
- Enjoy High-Definition (HD) images on a VGA monitor, projector or other display device
- Supports video resolutions up to 1920x1080p@60Hz, Full HD; Audio must be transferred separately
- Compliant with DisplayPort 1.2 Alternate Mode (DP Altmode)
- Plug and Play; requires no external power supply
- Compatible with all USB Type-C supported desktops, notebooks and tablets including Apple MacBook, Chromebook Pixel and more
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime Warranty

Specifications:

Standards and Certifications
• USB 3.1
• CE

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• FCC
• RoHS2
• WEEE

Connections
• USB type-C, 24-pin, male
• VGA, 15-pin, female
• Shielded

Video Resolutions
• VGA: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200@60Hz

Physical
• 32-AWG cable gauge
• Mylar and aluminum shielding
• Thermal plastic casing
• Length: 8 cm (3 in.)
• Weight: 31 g (1.1 oz.)
• Shielded
• Housing: ABS plastic

Operating Environment
• Operation Temperature: 32 ~ 122°F (0 ~ 50°C)
• Storage Temperature: -4 ~ 185°F (-40 ~ 85°C)
• Humidity (noncondensing): 0 ~ 96%

System Requirements
• Windows XP/Vista/7/8/8.1/10 or Linux or Mac 9.x/10.x or above

Package Contents
• SuperSpeed+ USB 3.1 to VGA Converter



For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.







For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.